



SYCOAT® 2020

Description

Core Shell Silane Modified
Acrylic Emulsion

Suggested Uses

- Finished topical, high gloss concrete coating
- No formulating needed
- Wood varnish
- Concrete sealers and stains

Characteristics

- Low VOC
- Small particle size
- Excellent water resistance
- Great penetration
- Excellent blush resistance
- Coatings made with Sycoat 2020 will demonstrate outstanding UV resistance
- Self-Crosslinking

Typical Physical Properties

Property	Value	
Percent Solids	41 to 43	
Polymer Type	Acrylic	
Brookfield Viscosity @ 25°C LVT #62 @ 12 rpm (cps.)	200 to 1,500	
pH	8.6 to 9.2	
Tg (°C)	46	
MFFT (°C)	3	
Density lbs./gallon @ 25 °C	8.8	
Particle Size (nm)	105	
Gloss	@ 20°	60.5
	@ 60°	84.5
Dispersion Type	Anionic	
Appearance (wet)	Milky White	
Odor	Slight Acrylic	




5618 Clyde Rhyne Drive
Sanford, NC 27330
Phone: 800-874-5878
Fax: 919-777-6695
stipolymer.com



SYCOAT® 2020

Core Shell Technology



Description

STI Polymer is the partner of choice for custom formulations and manufacturing of adhesives, paints and coatings. STI Polymer has built a reputation of proven performance, from providing manufacturers of paints and adhesives with the basic functional components of their formulations to producing private labeling of high-quality products for leading global corporations. STI's robust technical foundation and agility to meet the emerging needs, combined with an emphasis on long-term partnerships, drives its customer's successes.

STI Polymer

You drive. We navigate.



5618 Clyde Rhyne Drive
Sanford, NC 27330
Phone: 800-874-5878
Fax: 919-777-6695
stipolymer.com

General Properties

Recommended Storage:

Protect from freezing. Recommended storage temperature is 60°F to 80°F (15°C to 25°C). Keep in tightly covered container.

Shelf Life:

Twelve months from date of manufacture.

Packaging:

One-way drums and totes or bulk shipments available.

DOT Label Required:

This product is not classified as a hazardous product under this regulation. It does not contain any hazardous components at levels which have implications for labeling under these regulations.

Clean-up:

Soapy water (wet), Solvent (dry)

Material Safety Data Sheet:

Consult all information contained in the Safety Data sheet for this product.

Because we cannot anticipate nor control the many different conditions under which this information and our products may be used, we do not guarantee the applicability or the accuracy of this information or the suitability of our products in any given situation. Users of our product should make their own tests to determine the suitability of each such product for their particular purposes. The products discussed are sold without warranty, either express or implied, and the buyer assumes all responsibility for loss or damage arising from the handling or use of our products, whether done in accordance with directions or not. Also, statements concerning the possible use of our products are not intended as recommendations to use our products in the infringement of any patent.