SAITACK® 566

Description

Coater-ready two-part pressure sensitive acrylic adhesive specifically designed for removable applications.

Suggested Uses

- Removable tape and label adhesive for filmic and paper facestocks.

Characteristics

- Excellent adhesion to a variety of substrates.

- **APEO Free Product**

Typical Physical Properties

Property	Value
Percent Solids	48 to 50
Polymer Type	Acrylic
Brookfield Viscosity @ 25°C LVT #63 @ 12 rpm (cps.)	1,200 to 1,800
pH	7.5 to 8.5
Tg (°C)	-65
Density lbs./gallon @ 25° C	8.6
Dispersion Type	Anionic
Appearance (wet)	Milky White
Film Appearance (dry)	Clear
Odor	Slight Acrylic

Typical Performance Properties

Property	Value
Peel Adhesion 180° (stainless steel / 1 mil. PET, 1 mil. Dry, 20 min. dwell)	500 (g/25mm) 1.1 (lb./in.)
Static Shear (1'x1'x1kg @ 40°C)	50 (min)
Loop Tack	8 (oz.) 0.5 (lb.)

5618 Clyde Rhyne Drive
Sanford, NC 27330
Phone: 800-874-5878
Fax: 919-777-6695
stipolymer.com

© STIPolymer
REV10 December 18, 2023

SAITACK® 566

Description

STI Polymer is the partner of choice for custom formulations and manufacturing of adhesives, paints and coatings. STI Polymer has built a reputationof proven performance, from providing manufacturers of paintsand adhesiveswith the basic functionalcomponents of their formulations to producing private labelingof high-quality products for leading global corporations. STI's robust technical foundation and agility to meet the emerging needs, combinedwith an emphasis on long-term partnerships, drives its

General Properties

Recommended Storage:
Protect from freezing. Recommendedstorage temperature is 60°F to 80°F (15°C to 25°C). Keep in tightly covered container.

Shelf Life:
Six months from date of manufacture.

Packaging:
One-way drums and totes or bulk shipments available.

DOT Label Required:
This product is not classified as a hazardous product under this regulation. It does not contain any hazardous components at levels which have implications for labeling under these regulations.

Clean-up:
Soapy water (wet), Solvent (dry)

Material Safety Data Sheet:
Consult all information contained in the Safety Data sheet for this product.

Because we cannot anticipate nor control the many different conditions under which this information and our products may be used, we do not guarantee the applicability or the accuracy of this information or the suitability of our products in any given situation. Users of our product should make their own tests to determine the suitability of each such product for their particular purposes. The products discussed are sold without warranty, either express or implied, and the buyer assumes all responsibility for loss or damage arising from the handling or use of our products, whether done in accordance with directions or not. Also, statements concerning the possible use of our products are not intended as recommendations to use our products in the infringement of any patent.

5618Clyde Rhyne Drive
Sanford,NC 27330
Phone: 800-874-5878
Fax: 919-777-6695
stipolymer.com

© STIPolymer
REV10 December 18, 2023